


Easy Drilling in Various Types of Siding Boards.



A unique tip geometry which ensures safe cutting through nail embedded wood.



Characteristics

- Quick change system easily locks and unlocks cutter from shank.
- Specially designed for **safe** and fast drilling in nail embedded wood.
- Rotary only.
- Easy slug removal.

For use in

- Various types of Cement Siding and metallic siding, Nail embedded wood, FRP, PVC, and Artificial Marble.

Specifications

- Dia : 1" (25mm) - 8-1/4" (210mm)
- Drilling depth : 5-1/8" (130mm)
- Long shank (8") available for deeper drilling.
- Shank dia : Poly-clic shank "S" / "L"
S shank : 1" (25mm) - 1-3/4" (45mm).
L shank : 2" (50mm) - 8-1/4" (210mm).

WOODING CORE BIT (CARBIDE TEETH)



WOODING CORE BIT (CARBIDE TEETH)



Size Table

Set & Cutter

The actual sizes are in metric.

Nominal dia.(Inch)	Nominal dia.(mm)	Set	Cutter
		Part-No.	Part-No.
1	25	PCWS25	PCWS25C
1-1/8	29	PCWS29	PCWS29C
1-1/4	32	PCWS32	PCWS32C
1-3/8	35	PCWS35	PCWS35C
1-1/2	38	PCWS38	PCWS38C
1-3/4	45	PCWS45	PCWS45C
2	50	PCWS50	PCWS50C
2-1/8	55	PCWS55	PCWS55C
2-3/8	60	PCWS60	PCWS60C
2-9/16	65	PCWS65	PCWS65C
2-3/4	70	PCWS70	PCWS70C
2-7/8	75	PCWS75	PCWS75C
3-1/8	80	PCWS80	PCWS80C
3-1/2	90	PCWS90	PCWS90C
3-3/4	95	PCWS95	PCWS95C
3-7/8	100	PCWS100	PCWS100C
4-1/8	105	PCWS105	PCWS105C
4-3/4	120	PCWS120	PCWS120C
5-1/8	130	PCWS130	PCWS130C
6	155	PCWS155	PCWS155C
6-1/2	165	PCWS165	PCWS165C
7	180	PCWS180	PCWS180C
8-1/4	210	PCWS210	PCWS210C

Shank

Poly-clic shank	Part No.	For use with
S shank	PCSKS	1" - 1-3/4" (25mm - 45mm)
S shank SDS	PCSKSR	
S shank 200L (8")	PCSKS200	
S shank SDS 200L (8")	PCSKSR200	
L shank	PCSKL	2" - 8-1/4" (50mm - 210mm)
L shank SDS	PCSKLR	
L shank 200L (8")	PCSKL200	
L shank SDS 200L (8")	PCSKLR200	
SDS-max Shank (Rotary mode)	PCSKLMXK	

Center Drill

Item	Part-No.
Center Drill	PCWSCD225

Recommended Drill Speed / Wattage

Diameter inch (mm)	rpm	W
1 - 1-3/4 (25-45)	800 - 1500	over 450W
2 - 3-1/8 (50-80)	700 - 1100	over 550W
3-3/8 - 4-3/4 (85-120)	700 - 1100	over 650W
5-1/8 - 8-3/4(130-220)	500 - 1100	over 750W

 **MIYANAGA America Corp.**

40 Shuman Blvd.Suite 328
Naperville, Illinois 60563 USA
Tel:(630)778-3496 Fax:(630)778-3509

MIYANAGA CO.,LTD

Registered office and Factory-Japan
Representative Office-Europe

ISO 9001/ISO14001 Certified

www.miyanagaamerica.com

